



DECCOBOND 107

Packaging Glue

DESCRIPTION:

DECCOBOND 107 is a polymer based emulsion adhesive formulated for modern gluing operation where fast setting time with good bond strength is required. Dried films are elastomeric & flexible. It is suitable for machine application.

APPLICATION:

DECCOBOND 107 is suitable for packaging application, box manufacturing, seam & lap gluing, labelling & overlaying cardboard, where strong flexible bond is required.

PREPARATION & USAGE:

DECCOBOND 107 is supplied ready to use and do not require mixing.

Drying time: 5-10 minutes depending temperature condition & substrate

Set time: 2-4 hours

Ideal working temperature: Room temperature

CLEAN UP:

Tools, glue line, injection heads, glue guns and spreaders can be easily cleaned with water and sponge. Warm water cleans better. Keep application equipment in water after use for easier cleaning.

STORAGE:

DECCOBOND 107 is stable. Stores well for at least 9 to 12 months at room temperature of 20° C. Do not store next to heaters or very high temperatures of 65° C or more. **DECCOBOND 107** is packed in plastic or polyethylene containers. Do not store in unlined metal containers as there will be reactions between the adhesive and the unlined container resulting in dark stains and contaminants. **KEEP FROM FREEZING.**

VOC Compliant:



PHYSICAL PROPERTIES

Type	White emulsion	Viscosity	2,500 – 3,500 cps
Appearance	White	Odor	Mild to None
Solids	54– 55 %	Flammability	Non-flammable
Specific Gravity	1.10	VOC	2.0 g/L

PACKING INFORMATION

Size	Pail/Pallet
5 gallon pail	36
55 gallon drum	-
275 gallon tote	-



TENCO WESTECH POLYMERS INC.
160-6333 Graybar Road, Richmond, B.C.
Canada V6W 0C4 t 604-276-8538