



Since 1990

DECCO GLUE REMOVER

Professional Flooring Adhesive Remover

DESCRIPTION:

DECCO GLUE REMOVER is formulated with industrial strength formula to handle the toughest adhesive removal. **DECCO GLUE REMOVER** is the choice for professional flooring installer, including but not limited to general purpose spot and glue remover.

APPLICATION:

DECCO GLUE REMOVER is used to remove, residual Acrylic glue smudges, uncured Urethane glue, mastic & tar on floor, contact cement residue, tacky glue, tape & label residue, fabric & carpet spot remover, tree sap, wax, ideal for cleaning gluing tools, and many other general purpose cleaning.

PREPARATION & COVERAGE:

DECCO GLUE REMOVER is supplied ready to use and do not require mixing in a bottle of 275ml. Apply **DECCO GLUE REMOVER** on gooey area, stained, or tacky glue area. Allow a few minutes to work. Use a cloth to wipe clean.

For New Wood Floor

- Apply **DECCO GLUE REMOVER** on areas affected by excess glue, on areas where excess glue have oozed out, or on cured film after the installation of the Tongue and Groove floating floors. Use a cloth to wipe clean. **DECCO GLUE REMOVER** does not raise wood grain.

For Old Subfloor

- Apply **DECCO GLUE REMOVER** onto old surfaces and allow product to penetrate into old glue residue. Allow 5 to 10 minutes until glue residue softens. For tough mastics & old tar, a longer dwell time is



required. Penetration can be hastened by using a stiff brush. Remove softened glue with scraper or steel brush. Repeat process in stubborn areas.

Superior Quality. Revolutionary.

- Remove the Toughest Adhesives
- Professional Strength
- Sleek Packing
- Easy to Apply Cap

Applications

- Remove Residues
- Uncured Urethane
- Mastic & Tar
- Carpet & Fabric Spot
- Contact Cement Residue
- Tacky Glue, Tape & Label
- Tools Cleaning
- General Purpose Cleaning

* Trademark of Tenco Westtech Polymers Inc.

STORAGE:

DECCO GLUE REMOVER is stable. Stores well for at least 24 months at room temperature of 20° C. Do not store next to heaters or very high temperature of 30° C or more. **DECCO GLUE REMOVER** is packed in metal containers. **KEEP FROM FREEZING.**

PHYSICAL PROPERTIES			
Type	Liquid cleaner	Viscosity	50 cps
Appearance	Light amber liquid	Odor	Sweet orange
Vapor Pressure	2 mm Hg @ 20 degree C	Flammability	Yes, vapor accumulation can cause flash fires
Specific Gravity	0.82		46 degree C
Evaporation rate:	> 1	Flash Point	Method: Pensky-Martens closed tester
Boiling Point	160 degree C		

PACKING INFORMATION		
Size	Units/Case	Cases/Pallet
275 ml. Bottle	15	96



TENCO WESTECH POLYMERS INC.
 160-6333 Graybar Road, Richmond, B.C.
 Canada V6W 0C4 t 604-276-8538