



Since 1990

DECCOBOND 38

Wood Floor Repair Adhesive

DESCRIPTION:

DECCOBOND 38 Wood Floor Repair Adhesive is proprietary formulated (NOT the typical white wood glue or carpenter glue), solvent free, VOC free, eco-friendly, non-flammable, flows & fills voids easily, resilient after cured and remains elastomeric throughout the life of the floor, radiant heated floors compatible.

APPLICATION:

DECCOBOND 38 is used to repair defective floors. These floor defects are caused by gluedown flooring adhesives fail to perform, sub-floor not level, installation defects, water damages, wood floor quality creeping due to radiant heat cycling over time.

PREPARATION & USAGE:

DECCOBOND 38 is use together with **DECCO FIX-IT, Drill & Fill, Total Wood Floor Repair Kit.**



5 EASY STEPS

5-Easy steps to repair for flooring professionals & DIY. For instruction, please refer to **DECCO FIX-IT, Drill & Fill, Total Wood Floor Repair Kit** product data sheet.

CLEAN UP:

Tools can be easily cleaned with water & sponge. Warm water cleans better. To prevent damage, keep application equipment in water after use for easier cleaning.

STORAGE:

DECCOBOND 38 is stable. Stores well for at least 9 to 12 months at room temperature of 20° C. Do not store next to heaters or very high temperatures of 65° C or more. **DECCOBOND 38**



is packed in plastic or polyethylene containers.. **KEEP FROM FREEZING.**

VOC Compliant:

SCAQMD Rule #1168 (South Coast Air Quality Management District)



PACKING INFORMATION	
Size	Unit/Case
500 ml pint	6
4.0 liter Jug	4



TENCO WESTECH POLYMERS INC.
160-6333 Graybar Road, Richmond, B.C.
Canada V6W 0C4 t 604-276-8538